



5

10

15

20

25

30

the

pistol includes a breech or a magazine containing a cartridge, also placed in the axis of the striker.

Thus, the document WO 95/03844 discloses a device for injection by jet without needle, which is provided with an arming device activated by the rotation of a cap situated at one of the ends of the body of the said device.

13

The document WO 95/27523 describes a device for injection by jet without needle, provided at one of its ends with a cartridge formed in one piece.

The document WO 96/15821 describes a cartridge  
5 including a capsule on which a sleeve tube is fitted by force and induces stresses on the capsule.

Finally, the document EP 427 457 describes a device for injection by jet without needle, provided with a cartridge which cooperates at one of the ends of  
10 the device, by way of a component forming a breech.

Given the mode of action of the striker, which has a substantial kinetic energy before reaching the plunger of the cartridge, which can, in cases where the cartridge is not correctly arranged in the magazine of  
15 the pistol, cause it to burst at the start of the injection, these apparatuses are not reliable and are not easy to use if their use is infrequent.

The present invention is therefore aimed at overcoming these disadvantages by making available a  
20 device which is without magazine for a cartridge and which permits the injection by jet, without needle, of the product contained in a cartridge placed directly at the head of the said device, under strictly aseptic conditions, for a single use.

25 For this purpose, the cartridge for injection of a product, in particular a pharmaceutical product, by jet without needle, for single use, and intended to be fixed at a first end of the body of an injection device, the second end of the body receiving a cap  
30 which is able, by virtue of a relative movement of the body, to drive an arming device, cooperating with a percussion member intended to cooperate with the cartridge, is characterized in that it includes two elements:

35 - the first element made of glass forms the receptacle intended to contain the said product;

Other characteristics and advantages of the present invention will be evident from the description which follows, with reference being made to the attached drawings which show an illustrative embodiment of the invention, without this embodiment in any way being of a limiting character. In the figures:

[illegible]

Eno B17

- Figure 1 is a plan view, in front elevation and in section, of the device according to the invention, in the armed position;

5 - Figure 2 is a plan view, in front elevation and in section, of the device according to the invention, in the triggered position;

- Figure 3 is a view, on a larger scale and in section, of a cartridge containing a dose of injectable product;

10 - Figure 4 is a view illustrating another method of fixing the cartridge on the device;

- Figure 5 is a sectional view illustrating the movement of the striker on the elastomeric stopper contained in the cartridge;

15 - Figure 6 is a perspective view of the clamp system intended to hold the rod of the striker;

20 - Figure 7 is a plan view, in front elevation and in section, of the device according to another embodiment of the invention, including a releasable connection member;

- Figure 8 is a perspective view of the releasable connection member;

25 - Figure 9 is a plan view, in front elevation and in section, of the device according to the invention;

- Figure 10 is a plan view, in front elevation and in section, of a cartridge according to a second embodiment;

30 - Figure 11 is a plan view, in side elevation and in section, of a cartridge according to a second embodiment. *Detailed Description*

B

According to a preferred embodiment, the device which is the subject of the invention essentially comprises a body 1 extending in the form of a tube, in particular of straight cylindrical cross-section, intended to receive an arming device 2 connected to a cap 3, in particular knurled in order to improve its grip by the user, provided at one of the ends 4, 5 of the said body. *Viewing Fig. 8 the*

40 similar cross-section to that of the main body of the

B

said device, the diameter of which, however, is greater  
 in order to permit a relative rotational movement  
 thereof about the body, and it cooperates by way of a  
 catch device 6, in particular of the key type, with a  
 5 ring 7, itself integral with a clamp 8. The said ring  
 is engaged with play at the end of the body 1 and can  
 turn freely in the <sup>body</sup> ~~latter~~ its axial position in the  
 tube being determined by a radial abutment 9 on the  
 wall of the tube and fitting in a circular groove 10  
 10 formed on the said ring 7 and positioned opposite the  
 abutment 9. The rotational movement from the cap 3 is  
 transmitted to the ring by way of the catch device 6.  
 The said ring 7 is additionally provided with a central  
 recess 11 for the passage of a striker 12, free in  
 15 axial translation and leading inside the said clamp 8.  
 This clamp constitutes one of the links of the arming  
 device. Of overall cylindrical shape, it is equipped  
 with a plurality of cutouts 13 oriented substantially  
 parallel to the axis of the body in such a way as to  
 20 form a plurality of flexible tabs 14. <sup>(Fig. 6)</sup> In addition, the  
 inner bore 15 <sup>(Fig. 8)</sup> of the said clamp 8 is tapped in such a  
 way as to form impressions which can be screwed around  
 a threaded portion 16 provided on a rod 17 <sup>of the percussion</sup> ~~forming a~~  
 25 striker <sup>12</sup>. The thread pitch is determined as a function  
 of the chosen demultiplication and the stiffness  
 constant of a spring 18. The power of the striker can  
 also be adjusted by means of pre-setting the  
 compression of the spring, it being possible for the  
 space between the turns to be set by way of a knurled  
 30 wheel <sup>(as shown in Fig. 1)</sup> 46 displaced on the rod 17 and in contact with 18  
 or <sup>alternatively</sup> by way of a stack of washers arranged between the  
 spring 18 and a ring 25 <sup>as shown in Fig. 2</sup>. The turns of the spring 18 are  
 compressed by the relative rotational movement between  
 the cap 3 and the body 1.

35 According to an advantageous characteristic <sup>(Fig. 9)</sup> of  
 the invention, the cap 3 includes a safety device 47  
 which covers the rod of the striker 12. This safety  
 device 47 is connected to the cap 3 by way of a hinge  
 48 which permits a rotational movement of the latter  
 40 47, between a <sup>horizontal</sup> ~~locked~~ position and an <sup>safety device</sup> ~~unlocked~~ position  
 shown in dotted lines.

of the rod of the striker 12. The rotation of the safety device 47 <sup>to the horizontal position</sup> also makes it possible to act on the catch member 6 between the cap 3 and the ring 7. This is because it is essential that the user can arm the percussion device <sup>striker 12 and rod 17</sup> only when the safety device 47 is covering the rod of the striker 12; <sup>horizontal position</sup> this is why, when the safety device 47 is <sup>horizontal position</sup> locked on the cap 3, it acts on the catch member 6 in such a way that the latter permits the transmission of the rotational movement between the cap 3 and the ring 7.

When the safety device 47 <sup>B2</sup> is unlocked, <sup>vertical position</sup> that is to say when it is no longer covering the rod of the striker 12, it no longer acts on the catch member 6 and the user cannot arm the percussion device.

There is therefore a rod 17, forming a plunger, arranged inside the said body 1, its length being chosen in such a way that its end 19, <sup>extends towards the end</sup> not connected to the said clamp 8, <sup>B3</sup> is flush with one of the front surfaces 4, 5 of the body 1 when the arming device 2 is operational.

The peripheral envelope 20 of the clamp is held by a spacer sleeve 21, also of a cross-section similar to that of the body, the external diameter of which corresponds to the internal diameter of the body in such a way as to form guide zones. Its axial position inside the body being limited, on the one hand, at one of its ends 23, 24, by a pin 22 passing radially right through the striker 12, and, on the other hand, its other front end constituting a bearing surface for a spring 43; the axial position of the spring and its other bearing surface being additionally limited, for example, by a ring 25 inserted in the body, integral with the ~~said~~ rod 17 and axially immobilized, if appropriate, by a clip ring 26, or by a shoulder formed on the rod.

In the arming position, the user imparts a relative rotational movement between the body 1 and the cap 3; as we have seen above, the rotational movement of the cap is transmitted both to the said ring 7 and to the clamp 8 integral with the latter; the several

threads of the ~~said~~ clamp 8 in engagement with those of the rod make it possible to initiate the movement of translation between the rod 17 (forming the screw) and the clamp 8 (forming the nut) and the relative closing-together of these two components. This translation movement compresses the turns of the spring 18 until the space between the turns is reduced to the maximum. According to another embodiment, the spiral spring can be replaced by a helical spring or by any other elastic device.

In the disarm or trigger position, the user exerts a slight push on the striker 12, the pin 22, projecting radially and in contact with one of the front faces 23, 24 of the spacer sleeve, transmits a relative movement *(through slot 8a, Fig 8)* of translation between the spacer sleeve 21 and the clamp 8, which releases the end thereof from a conical bearing surface 27 provided at the bottom of the bore of the ~~said~~ spacer sleeve 21. The thrust of the spring 18 combined with the flexibility of the tabs of the clamp frees the respective threads previously in engagement, thereby provoking an almost impulse movement of translation of the whole rod.

According to another embodiment of the invention, *Figs. 7 and 8* there is arranged, between the cap 3 and the arming member integral with the clamp 8 contained in the body 1, a connection member 38 which permits the relative rotational movement between these two components only in one direction of rotation. The reason is that, to avoid any damage to the apparatus and to simplify its handling by the user, a releasable connection member 38 is provided which is composed principally of two components 39, 40, in particular of circular cross-section. One of the components 39 is integral with the cap 3, while the other 40 is connected to the clamp 8 and to the body 1 by way of a groove 44, and each of the components also has at their contact face, a plurality of raised zones *ratchets* 41. *Connection* These zones 41 have a profile which is able, on the one hand, to permit a relative sliding between the



components 39 and 40 in one direction of rotation between the cap 3 and the body 1 and, on the other hand, to transmit the moment in the other direction of rotation of the cap 3 relative to the body 1.

5 The raised zones 41 are preferably formed from a plurality of teeth, in particular of triangular cross-section.

For the connection member 38 to function, however, it is best not to suppress completely the movements of the components 39 and 40 in relation to the cap 3 and to the clamp 8; thus, when the connection member is active (released), it is necessary for the components 39, 40 to escape longitudinally from one another and for these components to return to their engaged position after suppression of the moment; for this reason, an elastic member <sup>41a</sup> 41, in particular of the spring type, is arranged in line with the outer surface of one of the components 39 or 40, in the area of a guide portion 42, which compensates for the translation movements between the components.

According to another characteristic of the invention, <sup>Figs. 9, 11</sup> a cartridge 28 is arranged at the other end 5 of the body 1 of the ~~said~~ device, by known means such as, in particular, being screwed on, clipped on (bushing, bayonet).

According to an advantageous characteristic of the invention, the cartridge 28 includes two elements 49, 50:

- the first element 49 forms the receptacle intended to contain the active principle, and it is obtained in particular from a type I medical-grade glass, since the receptacle is to contain injectable products;

- the second element 50 consists of an envelope of plastic material which covers the said first element 49.

The plastic material used in the overmoulding, that is to say covering, operation must be able to withstand a sterilization operation at high temperature (in the region of 120°C), must be approved for

pharmaceutical applications, must be insensitive to the temperature deviations in terms of its expansion, given that the cartridges 28 are generally stored in an atmosphere where the temperature is between 2 and 10°C.

5 Moreover, after overmoulding on the first element 49, the plastic material employed is translucent, even transparent, and can be tinted. The product called \_TPX\_ (polymethylpentene) will be chosen, for example, as the plastic material.

10 The first element 49 made of glass, and overall of substantially cylindrical shape, includes, at each end, an orifice 29, 30. One 30 of the orifices has a diameter substantially equivalent to the diameter of the rod 17, while the other 29, of small diameter, in  
 15 particular of the order of a few tenths of a <sup>millimeter</sup> ~~millimetre~~, serves as nozzle. The internal cavity of the said cartridge is filled under vacuum with an active principle 31 and is, if appropriate, covered with a film 32 of material compatible with the physico-  
 20 chemical properties of the said product, in order to limit to the maximum the phenomenon of adsorption.

The cartridge 28, thus formed by the overmoulding of a plastic material on a first element 49 made of glass, includes, at one of its ends, means  
 25 51 <sup>(Fig. 10)</sup> permitting the engagement and fixing of the ~~said~~ cartridge on the nose of the injection device.

The means 51 permitting the engagement and fixing are advantageously formed during the overmoulding operation by way of a plurality of studs 52  
 30 which project radially and are arranged along the diameter of the ~~said~~ cartridge 28, these studs cooperating with the bayonets provided at the end 53 of the injection device.

The other end 54 of the ~~said~~ cartridge 28 is  
 35 designed as a plane surface intended to be applied against the surface of the skin of the user.

The outlet orifice <sup>29</sup> ~~31~~ formed on this end 54 must be protected from possible contamination by the surrounding environment, and for this purpose there is

*BC* *an end* *center*  
 a cap 55 which is provided at its ~~center~~ <sup>center</sup> with an elastomeric seal 56, in particular of silicone.

According to another embodiment, a film covering the surface of the cartridge 28 is arranged on  
 5 the end 54.

*C*  
 This cap 55 is obtained by a process of moulding of plastic material, if appropriate, similar to that forming the cartridge.

*B*  
*end*  
 The cap 55 advantageously has lateral walls 57  
 10 which enclose the end of the ~~said~~ cartridge 28, the said walls 57 being provided, at their ends, with raised zones 58 allowing them to be clipped into impressions 59 provided on the outer lateral walls of the ~~said~~ cartridge 28, thus ensuring that the ~~cap~~ <sup>end</sup> cap 55 is  
 15 held on the cartridge.

*B*  
*end*  
 The upper wall 60 of the ~~cap~~ <sup>end</sup> cap 55 forms a grip zone which allows the user to position the studs 52 of the cartridge 28 in line with the bayonets of the injection device and, by a simple movement of rotation,  
 20 to block the studs 52 in the bayonets and, after blocking the studs 52, when the user continues to impart this rotational movement to the ~~cap~~ <sup>end</sup> cap 55 and thus to the cartridge 28 which is integral with it, to detach the lateral walls 57 of the ~~cap~~ <sup>end</sup> cap 55 from the  
 25 impressions 59 in the cartridge 28, in such a way as to make the injection device ready for use.

*C*  
 According to a first alternative, the elastomeric seal 56 is obtained during a simultaneous operation of moulding of the ~~cap~~ <sup>end</sup> cap 55.

*B*  
*end*  
 According to a second alternative, the elastomeric seal 56 is attached and fitted by force into ~~an orifice~~ <sup>a recess</sup> 61 provided on the internal wall 62 of the ~~cap~~ <sup>end</sup> cap 55.  
 30

*C*  
 According to another advantageous characteristic of the invention, it is intended to form a plurality of plastic material gaps in the thickness of the plastic overmould of the cartridge 28, in order to produce slots 63 for improving the visibility of the first element 49 made of glass. The cartridge 28 thus  
 35 obtained is for single use and is therefore disposable.  
 40

*12*

(Fig. 5)

After filling, the orifice 30 of the cartridge is closed off by a protective cover 33 in order to guarantee satisfactory aseptic conditions. It is also intended to interpose, between the dose of product contained in the cavity of the cartridge and the protective sealing cover, an elastomeric stopper 34 for enclosing the dose, this stopper 34 being intended to communicate to the liquid the pressure exerted by the plunger of a striker.

According to an advantageous characteristic of the invention, the plunger of the striker is driven a few <sup>millimeters</sup> into the body of the cartridge so that the percussion force is directed and <sup>centered</sup> in the axis of the elastomeric stopper 34, in order to prevent any risk of bursting of the first glass element forming the cartridge 28.

According to <sup>Fig. 3-5</sup> another embodiment of the cartridge 28, the <sup>cartridge</sup> latter is empty and is filled by the user just before use.

The outer envelope of the said cartridge moreover has, on the one hand, means of fixing 35, 35' to the said body (screw pitch, spike, etc.) and, on the other hand, raised zones 36 allowing it to be gripped by the user. The front face corresponding to the nozzle comprises, if appropriate, a basin 37 whose depth is variable but guarantees that the jet issuing from the orifice of the nozzle has the time needed to establish its hydrodynamics prior to the subcutaneous, intra-dermal or intramuscular injection.

The invention, as it has been described above, is very easy to use: there is no more sterilization, nor washing of the apparatus, while at the same time increased safety for the user is guaranteed because of the absence of a needle and the impossibility of reusing it without first having reloaded the apparatus with a new dose, the method of fixing the cartridge avoiding all the risks of the latter bursting because of the absence of a breach. This invention is advantageously adapted for use by a single user having no specific knowledge in the field of subcutaneous,

intradermal or intramuscular injections, and it reduces, on the one hand, the risks of accidents, which are always possible with an injection means having a needle, and, on the other hand, it eliminates the fear of stick injuries and any risk of contamination. The use of this device also allows the patient's chronobiology to be taken into consideration. This invention will have advantageous developments in the injection of a dose of small volume, in particular of 0.05 to 0.2 ml. It is of special interest for the administration of medicaments or vaccines to man or animals. Among other products which may be mentioned are polypeptides or peptides, such as enzymes and particularly calcitonin, used for the prevention of loss of bone substance and the treatment of osteoporosis, or else medicaments against migraine. Other products, in particular polypeptides or peptides, which may be administered using the device forming the subject of the invention, include hormones, such as insulin, somatostatin, the growth hormone, clotting factors, for example antihaemophilic factors, plasma components, such as erythropoietin, antiviral polypeptides, such as interferons, or immunomodulators, such as lymphokines. This device is also especially appropriate for the administration of vaccine preparations.

Of course, the present invention is not limited to the illustrative embodiments which have been described and represented above, but can encompass all variants thereof. Thus, the cartridges can be presented before the rod of the striker with the aid of a barrel or a charger, and they can also comprise the dose of the product to be injected.